

## 60X60X25 mm

## JF0625-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** :  $\pm 10\%$

### SPECIFICATIONS

| Model        | Bearing | Rated Voltage (V) | Operating Voltage (V) | Air Flow (CFM) | Static Pressure (inchH <sub>2</sub> O) | Speed (R.P.M.) | Input Current (Amp) | Input Power (Watt) | Nominal Power (Amp) | Noise (dBA) | Weight (g) |
|--------------|---------|-------------------|-----------------------|----------------|--|----------------|---------------------|--------------------|---------------------|-------------|------------|
| JF0625B1TRAL | B       | 12                | 10.2 ~ 13.8           | 36.24          | 0.578                                  | 7200           | 0.38                | 4.56               | 0.38                | 49.5        | 59         |
| JF0625B1TR   | B       |                   |                       | 29.69          | 0.422                                  | 6000           | 0.37                | 4.44               | 0.38                | 42.5        |            |
| JF0625B1UR   | B,H     |                   |                       | 26.96          | 0.357                                  | 5500           | 0.29                | 3.48               | 0.30                | 39.6        |            |
| JF0625-1S    | B,H, S  |                   |                       | 24.27          | 0.292                                  | 5000           | 0.22                | 2.64               | 0.22                | 37.2        |            |
| JF0625-1H    | B,H, S  |                   |                       | 21.44          | 0.237                                  | 4500           | 0.20                | 2.40               | 0.23                | 34.1        |            |
| JF0625-1M    | B,H, S  |                   |                       | 19.00          | 0.185                                  | 4000           | 0.16                | 1.92               | 0.20                | 31.3        |            |
| JF0625-1L    | B,H, S  |                   |                       | 16.76          | 0.145                                  | 3500           | 0.13                | 1.56               | 0.17                | 27.3        |            |
| JF0625-1E    | B,H, S  |                   |                       | 14.24          | 0.108                                  | 3000           | 0.11                | 1.32               | 0.11                | 22.4        |            |
| JF0625-1V    | B,H, S  |                   |                       | 11.72          | 0.076                                  | 2500           | 0.08                | 0.96               | 0.08                | 20.2        |            |
| JF0625B2TRAJ | B       | 24                | 20.4 ~ 27.6           | 35.15          | 0.552                                  | 7000           | 0.21                | 5.04               | 0.21                | 48.3        |            |
| JF0625B2TR   | B       |                   |                       | 29.69          | 0.422                                  | 6000           | 0.20                | 4.80               | 0.21                | 42.5        |            |
| JF0625B2UR   | B,H     |                   |                       | 26.96          | 0.357                                  | 5500           | 0.16                | 3.84               | 0.16                | 39.6        |            |
| JF0625-2S    | B,H     |                   |                       | 24.27          | 0.292                                  | 5000           | 0.13                | 3.12               | 0.14                | 37.2        |            |
| JF0625-2H    | B,H, S  |                   |                       | 21.44          | 0.237                                  | 4500           | 0.12                | 2.88               | 0.17                | 34.1        |            |
| JF0625-2M    | B,H, S  |                   |                       | 19.00          | 0.185                                  | 4000           | 0.11                | 2.64               | 0.13                | 31.3        |            |
| JF0625-2L    | B,H, S  |                   |                       | 16.76          | 0.145                                  | 3500           | 0.10                | 2.40               | 0.12                | 27.3        |            |
| JF0625-2E    | B,H, S  |                   |                       | 14.24          | 0.108                                  | 3000           | 0.07                | 1.68               | 0.07                | 22.4        |            |
| JF0625-2V    | B,H, S  |                   |                       | 11.72          | 0.076                                  | 2500           | 0.06                | 1.44               | 0.06                | 20.2        |            |
| JF0625B4UR   | B,H     | 48                | 40.8 ~ 55.2           | 26.96          | 0.357                                  | 5500           | 0.11                | 5.28               | 0.11                | 39.6        |            |
| JF0625B4SR   | B,H     |                   |                       | 24.27          | 0.292                                  | 5000           | 0.09                | 4.32               | 0.09                | 37.2        |            |
| JF0625B4HR   | B,H, S  |                   |                       | 21.44          | 0.237                                  | 4500           | 0.07                | 3.36               | 0.08                | 34.1        |            |
| JF0625B4MR   | B,H, S  |                   |                       | 19.00          | 0.185                                  | 4000           | 0.06                | 2.88               | 0.07                | 31.3        |            |
| JF0625B4LR   | B,H, S  |                   |                       | 16.76          | 0.145                                  | 3500           | 0.05                | 2.40               | 0.06                | 27.3        |            |

Specifications subject to change without notice

The 7<sup>th</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".

Please contact us for detail if your request bearing system is not shown in the above list.

