

EE CORE

| TYPE | FIG. | Dimensions(mm) | | | | | |
|---------------|------|----------------|------------|------------|------------|-------------|------------|
| | | A | B | C | D | E | F |
| EE5/5/2 | 1 | 5.25±0.2 | 2.65±0.15 | 1.95±0.1 | 1.35±0.1 | 3.8min | 2.0±0.15 |
| EE6.3/6.7/1.2 | 1 | 6.3±0.3 | 3.35±0.1 | 1.2±0.2 | 1.75±0.2 | 4.2min | 2.1±0.1 |
| EE8.3/8/4 | 1 | 8.7±0.3 | 4.1±0.2 | 3.9±0.2 | 1.85±0.15 | 6.1min | 3.1±0.2 |
| EE10/11/5 | 1 | 10.2±0.3 | 5.5±0.15 | 4.85±0.2 | 2.5±0.15 | 7.5min | 4.3±0.15 |
| EE10/11/10 | 1 | 10.5±0.5 | 5.5±0.15 | 9.8±0.3 | 2.4±0.3 | 7.6min | 4.3±0.2 |
| EE12/13/4 | 1 | 11.9±0.4 | 6.5±0.3 | 3.7±0.2 | 2.5±0.2 | 8.6min | 4.9±0.3 |
| EE13/13/4 | 1 | 12.7±0.35 | 6.35±0.15 | 3.6±0.2 | 3.6±0.2 | 8.8min | 4.65±0.15 |
| EE13/12/6 | 1 | 13.0±0.4 | 6.0±0.15 | 6.0±0.15 | 2.6±0.2 | 9.8min | 4.7±0.3 |
| EE13/13/6 | 1 | 13.2±0.4 | 6.3±0.3 | 6.0±0.3 | 2.7±0.3 | 10.0min | 4.7±0.3 |
| EE13/13/10 | 1 | 13.2±0.4 | 6.3±0.3 | 9.8±0.3 | 2.7±0.3 | 9.8min | 4.7±0.3 |
| EE16/12/5 | 1 | 16.1±0.6 | 6.1±0/-0.3 | 4.7±0/-0.4 | 4.7±0/-0.3 | 11.45min | 3.8±0.2 |
| EE16/12/7 | 1 | 16.0±0.35 | 6.0±0.15 | 7.2±0.2 | 4.55±0.2 | 11.3min | 3.85±0.15 |
| EE16/14/7 | 1 | 16.0±0.5 | 7.3±0.3 | 6.7±0.3 | 4.0±0.3 | 11.8min | 5.2±0.3 |
| EE16/15/5 | 1 | 16.0±0.5 | 7.3±0.3 | 5.0±0.3 | 4.0±0.3 | 11.8min | 5.2±0.3 |
| EE16/16/5 | 1 | 16.2±0.6 | 8.1±0.3 | 4.5±0.3 | 4.5±0.3 | 11.4min | 5.9±0.3 |
| EE16/16/7 | 1 | 16.0±0.5 | 8.2±0.2 | 7.0±0.3 | 4.6±0.3 | 11.2min | 6.0±0.2 |
| EE16/16/8 | 1 | 16.0±0.7/-0.5 | 8.2±0/-0.3 | 8.2±0/-0.3 | 4.7±0/-0.3 | 11.3±0.6/-0 | 5.7±0.4/-0 |
| EE16/25/5 | 1 | 16.0±0.4 | 12.5±0.2 | 4.8±0.2 | 4.0±0.2 | 11.7min | 10.35±0.2 |
| EE19/16/5 | 1 | 19.0±0.4 | 8.0±0.15 | 4.8±0.2 | 4.75±0.2 | 13.8min | 5.8±0.15 |
| EE19/16/7 | 1 | 19.2±0.3 | 8.2±0.2 | 6.7±0.3 | 4.7±0.2 | 14.4min | 5.9±0.2 |
| EE19/16/10 | 1 | 19.2±0.5 | 8.1±0.3 | 9.5±0.3 | 4.6±0.3 | 14.2min | 5.8±0.3 |
| EE19/20/5 | 1 | 19.1±0.5 | 9.9±0.25 | 5.0±0.5 | 4.55±0.5 | 14.0min | 7.6±0.15 |
| EE19/27/5 | 1 | 19.1±0.3 | 13.55±0.25 | 5.0±0.2 | 4.7±0.3 | 14.0min | 11.15±0.35 |
| EE20/20/6 | 1 | 20.0±0.5 | 10.1±0.3 | 5.7±0.3 | 5.7±0.3 | 14.1min | 7.6±0.3 |
| EE20/20/9 | 1 | 20.0±0.6 | 9.9±0.2 | 8.8±0.25 | 5.7±0.2 | 14.1min | 7.2±0.2 |
| EE20/20/11 | 1 | 20.0±0.4 | 10±0.15 | 10.8±0.3 | 5.7±0.2 | 14.1min | 7.2±0.15 |
| EE20/21/7 | 1 | 20.5±0.5 | 10.7±0.3 | 7.0±0.3 | 5.0±0.3 | 14.7min | 7.0±0.3 |
| EE20/28/5 | 1 | 20.1±0.5 | 13.9±0.3 | 4.8±0.3 | 4.8±0.3 | 14.6min | 11.7±0.3 |
| EE22/19/6 | 1 | 22.4±0.5 | 9.5±0.4 | 5.65±0.25 | 5.65±0.25 | 16.0min | 5.6±0.4 |
| EE22/30/6 | 1 | 22.0±0.4 | 15.0±0.4 | 5.75±0.25 | 5.75±0.25 | 15.6min | 11.3±0.2 |
| EE22/44/5 | 1 | 22.2±0.4 | 22.2±0.4 | 4.7±0.3 | 5.8±0.3 | 15.6min | 18.2±0.2 |


EE CORE

FIG.1

| Cl (mm ³) | Ae (mm ²) | Le (mm) | Ve (mm ³) | AL ± 25%(nH/N ²) | | | | | | Weight g/PRS |
|--------------------------|--------------------------|------------|--------------------------|------------------------------|------|------|------|------|---------|-----------------|
| | | | | FW40 | FW44 | FW95 | FW5K | FW7K | FW10K | |
| 5.01 | 2.53 | 12.68 | 32.1 | 250 | 260 | 290 | 400 | 530 | 960min | 0.20 |
| 6.17 | 2.31 | 14.27 | 33.0 | 200 | 210 | 240 | | | | 0.18 |
| 2.75 | 7.00 | 19.20 | 134.0 | 550 | 555 | 650 | 1200 | 1300 | 1500min | 0.70 |
| 2.23 | 11.81 | 26.30 | 310.6 | 800 | 850 | 1000 | 1700 | 2000 | 2300min | 1.50 |
| 1.1 | 23.10 | 26.40 | 611.6 | 1900 | 1900 | | | | | 3.20 |
| 3.19 | 9.25 | 29.55 | 352.3 | | | | | | 3000min | 1.80 |
| 2.34 | 12.68 | 29.62 | 375.5 | 800 | 800 | 1000 | 1530 | 1780 | 2240min | 1.90 |
| 1.92 | 15.90 | 30.61 | 486.8 | 980 | 980 | 1150 | 1500 | 1750 | 2150min | 1.20 |
| 1.86 | 16.20 | 30.20 | 586.0 | 1000 | 1000 | 1500 | 2200 | 2700 | 3100min | 2.70 |
| 1.13 | 26.46 | 29.95 | 975.0 | 2200 | 2330 | | | | | 3.50 |
| 1.52 | 19.28 | 29.39 | 566.8 | 1160 | 1200 | 1450 | | | | 2.92 |
| 0.93 | 31.62 | 29.36 | 928.3 | 2010 | 2050 | 2500 | | | | 4.80 |
| 1.44 | 26.20 | 37.90 | 993.0 | 1130 | 1220 | 1500 | | | | 4.60 |
| 1.8 | 19.00 | 34.80 | 670.0 | 1100 | 1170 | 1250 | 2400 | 2800 | 3200min | 3.30 |
| 1.87 | 20.10 | 37.60 | 754.0 | 1000 | 1070 | 1320 | 2300 | 2800 | 3200min | 3.90 |
| 1.05 | 34.20 | 38.40 | 1033.4 | 1200 | | | | | | 5.80 |
| 1.03 | 36.33 | 37.56 | 1364.7 | 1900 | 1950 | 2400 | | | | 6.86 |
| 2.78 | 20.01 | 55.67 | 1114.0 | 800 | 770 | | | | | 5.10 |
| 1.79 | 22.28 | 39.81 | 886.9 | 1150 | 1200 | 1450 | 1950 | 2300 | 3300min | 4.40 |
| 1.34 | 30.30 | 40.80 | 1236.0 | 1500 | 1520 | 1850 | | | | 6.30 |
| 0.9 | 44.50 | 39.90 | 1777.5 | 1700 | 2250 | 2800 | | | | 9.20 |
| 2.08 | 22.90 | 47.60 | 1090.0 | 950 | 1060 | 1320 | | | | 6.80 |
| 2.78 | 22.40 | 62.20 | 1393.0 | 830 | 860 | 1100 | 1800 | 2300 | 2800min | 7.00 |
| 1.38 | 31.00 | 43.00 | 1340.0 | 1250 | 1600 | 1950 | | | | 7.50 |
| 0.96 | 48.06 | 46.32 | 2226.0 | 2170 | 2220 | 2800 | | | | |
| 0.77 | 60.46 | 46.39 | 2804.6 | 2800 | 2900 | 3600 | | | | 14.2 |
| 1.20 | 39.29 | 47.09 | 1850.2 | 1600 | 1650 | 2070 | 3600 | 4200 | 5800min | 9.70 |
| 2.55 | 24.50 | 62.74 | 1541.8 | 860 | 880 | 1130 | 2800 | 3500 | 4200min | 8.40 |
| 1.29 | 31.92 | 41.22 | 1749.2 | 1790 | 1900 | 2350 | 3900 | 4700 | 5600min | 7.00 |
| 1.82 | 35.00 | 63.60 | 2220.0 | 1300 | 1230 | 1570 | 2800 | 3500 | 4200min | 11.1 |
| 3.15 | 29.60 | 93.20 | 2757.0 | 650 | 750 | 970 | | | | 13.80 |

EE CORE



| TYPE | FIG. | Dimensions(mm) | | | | | |
|------------|------|----------------|------------|-----------|-----------|----------|------------|
| | | A | B | C | D | E | F |
| EE23/18/8 | 1 | 23.0±0.4 | 9.0±0.15 | 8.2±0.2 | 7.2±0.2 | 16.6min | 5.4±0.15 |
| EE25/20/6 | 1 | 25.4±0.5 | 10.0±0.3 | 6.4±0.3 | 6.0±0.3 | 18.5min | 7.0±0.3 |
| EE25/14/14 | 1 | 25.00±0.4 | 7.25±0.15 | 13.8±0.30 | 7.2±0.25 | 17.6min | 2.05±0.15 |
| EE25/18/11 | 1 | 25.05±0.75 | 9.0±0.25 | 10.75±0.3 | 7.25±0.25 | 17.8min | 5.4±0.25 |
| EE25/25/9 | 1 | 25.05±0.75 | 12.55min | 8.85±0.25 | 7.25±0.25 | 17.5min | 9.0min |
| EE25/26/7 | 1 | 25.05±0.75 | 12.55±0.25 | 7.2±0.3 | 7.25±0.25 | 17.5min | 8.95±0.25 |
| EE25/26/11 | 1 | 25.05±0.5 | 12.55±0.15 | 10.75±0.3 | 7.25±0.25 | 17.5min | 8.95±0.15 |
| EE25/32/6 | 1 | 25.4±0.5 | 16.3±0.4 | 6.3±0.3 | 6.3±0.3 | 18.6min | 13.3±0.4 |
| EE26/22/11 | 1 | 26.7±0.5 | 10.8±0.3 | 11.0±0.3 | 7.2±0.3 | 19.0min | 6.8±0.3 |
| EE28/21/11 | 1 | 28.40±0.5 | 10.30±0.2 | 10.70±0.3 | 7.20±0.3 | 20.0min | 6.30±0.2 |
| EE28/34/11 | 1 | 28.2±0.5 | 17.1±0.3 | 10.4±0.3 | 7.1±0.3 | 18.9min | 12.8±0.4 |
| EE30/26/11 | 1 | 30.0±0.5 | 13.2±0.2 | 10.7±0.3 | 10.7±0.3 | 19.8min | 8.1±0.2 |
| EE30/30/7 | 1 | 30.0±0.7 | 15.0±0.2 | 7.05±0.25 | 6.95±0.25 | 19.6min | 10.0±0.2 |
| EE32/33/9 | 1 | 32.1±0.6 | 16.7±0.15 | 9.15±0.3 | 9.2±0.3 | 22.7min | 11.5±0.15 |
| EE32/32/11 | 1 | 32.1±0.6 | 16.1±0.15 | 10.45±0.3 | 9.2±0.3 | 23.2±0.6 | 11.75±0.15 |
| EE33/28/13 | 1 | 33.0±0.6 | 14.0±0.3 | 13.0±0.6 | 9.7±0.3 | 22.8min | 9.6±0.3 |
| EE33/48/13 | 1 | 33±0.65 | 23.7±0.15 | 12.7±0.35 | 9.7±0.3 | 23.8min | 19.2±0.15 |
| EE35/29/10 | 1 | 35.0±0.5 | 14.5±0.25 | 10.0±0.4 | 9.5±0.3 | 25.0min | 10.0±0.3 |
| EE35/35/10 | 1 | 35.0±0.6 | 17.5±0.3 | 10.0±0.3 | 10.0±0.3 | 24.5min | 12.5±0.3 |
| EE40/35/12 | 1 | 40.0±0.7 | 17.5±0.4 | 11.7±0.4 | 11.5±0.4 | 27.2min | 10.6±0.4 |
| EE41/34/13 | 1 | 40.6±0.6 | 16.5±0.3 | 12.5±0.3 | 12.5±0.3 | 28.6min | 10.5±0.3 |
| EE42/42/15 | 1 | 42.1±0.9 | 21.2±0.4 | 14.9±0.3 | 12.0±0.3 | 29.5min | 15.4±0.3 |
| EE42/42/20 | 1 | 42.1±0.9 | 21.2±0.4 | 19.9±0.3 | 12.0±0.3 | 29.5min | 15.4±0.3 |
| EE51/54/12 | 1 | 50.5±1.0 | 26.8±0.2 | 12.0±0.3 | 16.0±0.25 | 33.9min | 18.8±0.2 |
| EE55/55/17 | 1 | 55.0±1.0 | 27.5±0.3 | 17.0±0.7 | 16.7±0.3 | 37.0min | 18.8±0.3 |
| EE55/55/21 | 1 | 55.0±1.0 | 27.7±0.3 | 20.9±0.5 | 16.9±0.3 | 37.5min | 18.8±0.3 |
| EE56/55/25 | 1 | 56.5±1.0 | 27.8±0.3 | 24.8±0.3 | 16.85±0.3 | 37.5min | 19.0±0.3 |
| EE65/65/20 | 1 | 65.4±1.6 | 32.6±0.6 | 19.8±0.7 | 19.8±0.7 | 44.2min | 22.6±0.6 |
| EE65/65/27 | 1 | 65.4±1.6 | 32.6±0.6 | 27.0±0.6 | 19.8±0.7 | 44.2min | 22.6±0.6 |
| EE70/66/32 | 1 | 70.0±1.5 | 33.0±0.3 | 31.75±0.8 | 21.5±0.6 | 48.0min | 22.5±0.3 |
| EE80/76/20 | 1 | 80.5±1.5 | 38.0±0.4 | 20.0±0.5 | 20.0±0.4 | 60.0min | 28.0±0.3 |

EE CORE




FIG.1

| Cl (mm ³) | Ae (mm ²) | Le (mm) | Ve (mm ³) | AL ± 25%(nH/N ²) | | | | | | Weight g/PRS |
|--------------------------|--------------------------|------------|--------------------------|------------------------------|-------|-------|------|-------|----------|-----------------|
| | | | | FW40 | FW44 | FW95 | FW5K | FW7K | FW10K | |
| 0.72 | 59.00 | 42.60 | 2548.0 | 2500 | | | | | | 13.50 |
| 1.28 | 38.40 | 49.50 | 2131.0 | 1900 | 1650 | 2070 | 4100 | 5100 | 6000 | 10.70 |
| 0.29 | 99.36 | 29.40 | 4414.0 | 4800 | | | | | | 22.00 |
| 0.56 | 77.30 | 43.60 | 3371.0 | 3200 | | | | | | 20.30 |
| 0.93 | 62.69 | 58.51 | 3667.9 | 2350 | 2430 | 3100 | | | | 19.00 |
| 1.06 | 54.00 | 57.60 | 3267.0 | 1900 | 1980 | 2500 | | | | 13.50 |
| 0.75 | 76.99 | 57.81 | 4451.0 | 3000 | 3100 | 3950 | | | | 22.40 |
| 1.90 | 40.40 | 76.70 | 3097.0 | 1300 | 1300 | | 2800 | 3600 | 4300 | 15.50 |
| 0.62 | 79.20 | 49.80 | 4578.0 | 3600 | 3600 | | | | | 22.00 |
| 0.63 | 77.00 | 48.80 | 4534.0 | 3500 | 3690 | 4630 | | | | 24.00 |
| 0.99 | 73.84 | 73.65 | 6888.0 | 2400 | 2500 | 3230 | | | | 35.00 |
| 0.53 | 110.00 | 57.80 | 6358.0 | 4100 | 4230 | 5370 | | | | 35.00 |
| 1.28 | 48.90 | 63.00 | 4561.0 | 2300 | 1750 | 2240 | 4600 | | | 23.60 |
| 0.88 | 85.44 | 75.08 | 6414.5 | 2700 | 2800 | 3600 | 5050 | 6100 | 7600min | 32.60 |
| 0.80 | 93.47 | 74.91 | 7001.8 | 2950 | 3100 | 3950 | | | | 35.20 |
| 0.56 | 118.83 | 66.50 | 7901.8 | 3900 | 4040 | 5170 | | | | 40.60 |
| 0.92 | 114.88 | 105.47 | 12115.9 | 2750 | 2850 | 3700 | | | | 60.60 |
| 0.70 | 98.60 | 69.20 | 6820.0 | 2593 | 2684 | 3430 | 5550 | 6700 | 8400min | 33.20 |
| 0.81 | 99.69 | 84.77 | 8047.5 | 2950 | 3050 | 3950 | | | | 40.80 |
| 0.55 | 141.80 | 78.68 | 11161.0 | 4300 | 4390 | 5660 | | | | 59.00 |
| 0.52 | 149.22 | 77.41 | 11551.4 | 4400 | 4560 | 5870 | 8890 | 10800 | 13300min | 59.30 |
| 0.60 | 180.00 | 97.80 | 17600.0 | 3800 | 4560 | 5940 | | | | 88.00 |
| 0.40 | 242.00 | 97.80 | 24698.0 | 5000 | 6070 | 7900 | | | | 120.00 |
| 0.62 | 192.00 | 118.80 | 22866.0 | 4700 | 4500 | | | | | 120.00 |
| 0.428 | 283.00 | 121.00 | 37810.0 | 5500 | 3700 | | | | | 178.00 |
| 0.35 | 354.00 | 123.00 | 43542.0 | 6500 | 7350 | 9660 | | | | 223.00 |
| 0.29 | 417.00 | 122.00 | 58446.0 | 7770 | | | | | | 308.00 |
| 0.40 | 378.90 | 147.00 | 58655.0 | 5400 | 5900 | 7840 | | | | 285.00 |
| 0.274 | 540.00 | 147.00 | 79000.0 | 7900 | 9700 | 12800 | | | | 410.00 |
| 0.208 | 700.00 | 145.50 | 101900.0 | 12800 | 12200 | 16100 | | | | 530.00 |
| 0.446 | 399.00 | 183.50 | 73150.0 | 4500 | 5880 | 7840 | | | | 368.00 |

EE CORE

| TYPE | FIG. | Dimensions(mm) | | | | | |
|----------------|------|----------------|-----------|----------|----------|-----------|-------------|
| | | A | B | C | D | E | F |
| EE85/87/26 | 1 | 85.0±1.2 | 43.5±0.5 | 26.0±0.6 | 26.4±0.6 | 56.0min | 30.5±0.5 |
| EE85/88/32 | 1 | 85.0±1.5 | 44.0±1.0 | 31.5±0.5 | 26.8±0.5 | 55.0min | 29.0±1.5/-0 |
| EE100/120/28 | 1 | 100.0±2.0 | 60.0±0.6 | 28.0±1.0 | 28.0±1.0 | 71.5min | 46.5±1.2 |
| EE110/110/36 | 1 | 110.0±2.0 | 55.0±0.6 | 36.0±1.0 | 36.0±1.0 | 75.0min | 38.0±0.2 |
| EE110/114/18.5 | 1 | 110.0±2.5 | 57.0±0.5 | 18.5±0.5 | 36.0±0.4 | 110.0±2.5 | 39.0±0.5 |
| EE118/173/35 | 1 | 118.0±1.5 | 86.5±0.5 | 35.0±0.4 | 35.0±0.4 | 118.0±1.5 | 69.0±0.5 |
| EE120/90/30 | 1 | 120.0±1.5 | 45.0±0.5 | 30.0±0.5 | 29.0±0.5 | 88.0±1.5 | 30.0±0.5 |
| EE128/128/40 | 1 | 128.0±2.0 | 64.0±0.5 | 40.0±0.5 | 40.0±0.5 | 88.0±1.5 | 44.0±0.5 |
| EE130/128/40 | 1 | 130.0±2.0 | 64.0±0.5 | 40.0±0.5 | 40.0±0.5 | 90.0±1.5 | 44.0±0.5 |
| EE140/136/40 | 1 | 140.0±2.0 | 68.0±0.5 | 40.0±0.5 | 40.0±0.5 | 100.0±1.5 | 48.0±0.5 |
| EE160/160/40 | 1 | 160.0±2.5 | 80.0±0.75 | 40.0±0.5 | 40.0±0.5 | 116.0±1.5 | 60.0±0.75 |
| EE160/170/40 | 1 | 160.0±2.5 | 85.0±0.75 | 40.0±0.5 | 40.0±0.5 | 116.0±1.5 | 65.0±0.75 |
| EE160/250/40 | 1 | 162.0±3.0 | 125.0±0.5 | 40.0±0.5 | 58.0±1.5 | 101.0±1.5 | 95.0±0.5 |
| EE180/250/40 | 1 | 180.0±3.0 | 125.0±0.5 | 40.0±0.5 | 60.0±1.5 | 120.0±2.5 | 95.0±0.5 |
| EE188/154/27 | 1 | 188.0±2.5 | 77.0±1.0 | 27.0±0.5 | 54.0±1.3 | 126.0±2.5 | 49.0±1.0 |
| EE188/154/54 | 1 | 188.0±2.5 | 77.0±1.0 | 54.0±0.5 | 54.0±1.3 | 126.0±2.5 | 49.0±1.0 |
| EE193/158/30 | 1 | 193.0±4.0 | 79.0±1.0 | 30.0±0.5 | 59.0±2.0 | 132.0±2.5 | 49.0±1.0 |
| EE200/160/40 | 1 | 200.0±4.0 | 80.0±1.0 | 40.0±0.5 | 40.0±0.7 | 158.0±3.0 | 60.0±1.0 |
| EE210/190/40 | 1 | 210.0±4.0 | 95.0±0.5 | 40.0±0.5 | 60.0±1.0 | 150.0±3.0 | 65.0±0.5 |
| EE230/188/28 | 1 | 230.0±4.0 | 94.0±1.0 | 28.0±0.5 | 60.0±1.5 | 172.0±3.0 | 63.0±1.0 |
| EE240/232/40 | 1 | 240.0±4.0 | 116.0±4.0 | 40.0±0.5 | 60.0±2.0 | 176.0±3.0 | 86.0±4.0 |
| EE250/226/40 | 1 | 250.0±4.0 | 113.0±0.5 | 40.0±0.5 | 60.0±2.0 | 186.0±3.0 | 83.0±0.5 |
| EE260/182/40 | 1 | 260.0±4.0 | 91.0±0.5 | 40.0±0.5 | 59.0±2.0 | 200.0±4.0 | 63.0±0.5 |
| EE320/320/40 | 1 | 320.0±6.0 | 160.0±0.5 | 40.0±0.5 | 80.0±2.0 | 236.0±4.0 | 120.0±0.5 |
| EE480/320/40 | 1 | 480.0±7.0 | 160.0±0.5 | 40.0±0.5 | 80.0±2.0 | 400.0±6.0 | 120.0±0.5 |
| EE640/320/40 | 1 | 640.0±10/-5 | 160.0±0.5 | 40.0±0.5 | 80.0±1.5 | 560.0±6.0 | 120.0±0.5 |


EE CORE

FIG.1

| Cl | Ae | Le | Ve | AL ± 25% (nH/N ²) | | | | | | Weight g/PRS |
|--------|---------|---------|-----------|-------------------------------|------|------|------|------|-------|-----------------|
| | | | | FW40 | FW44 | FW95 | FW5K | FW7K | FW10K | |
| 0.27 | 686.00 | 196.30 | 145320.0 | 7500 | | | | | | 700.00 |
| 0.218 | 844.00 | 184.00 | 184098.0 | 11800 | | | | | | 880.00 |
| 0.349 | 775.00 | 271.00 | 222726.0 | 10000 | | | | | | 1028.00 |
| 0.19 | 1282.00 | 243.10 | 311810.0 | 10000 | | | | | | 1796.50 |
| 0.375 | 666.00 | 250.00 | 174270.0 | 7000 | | | | | | 830.00 |
| 0.31 | 1225.00 | 375.00 | 487480.0 | 8500 | | | | | | 2320.00 |
| 0.255 | 870.00 | 223.00 | 217800.0 | 10200 | | | | | | 1050.00 |
| 0.177 | 1600.00 | 284.00 | 486400.0 | 14000 | | | | | | 2330.00 |
| 0.179 | 1600.00 | 286.00 | 489600.0 | 14000 | | | | | | 2340.00 |
| 0.195 | 1600.00 | 312.00 | 531200.0 | 13000 | | | | | | 2550.00 |
| 0.235 | 1600.00 | 376.00 | 659200.0 | 10800 | | | | | | 3160.00 |
| 0.247 | 1600.00 | 396.00 | 692800.0 | 10500 | | | | | | 3320.00 |
| 0.219 | 2320.00 | 511.00 | 1293200.0 | 12000 | | | | | | 6250.00 |
| 0.22 | 2400.00 | 530.00 | 1344000.0 | 13091 | | | | | | 6451.00 |
| 0.239 | 1458.00 | 349.00 | 591192.0 | 10700 | | | | | | 2830.00 |
| 0.118 | 2916.00 | 349.00 | 1182384.0 | 21500 | | | | | | 5650.00 |
| 0.201 | 1770.00 | 358.00 | 700200.0 | 13000 | | | | | | 3370.00 |
| 0.261 | 1600.00 | 418.00 | 713600.0 | 10000 | | | | | | 3420.00 |
| 0.183 | 2400.00 | 440.00 | 1128000.0 | 13750 | | | | | | 5400.00 |
| 0.27 | 1680.00 | 454.00 | 815584.0 | 9500 | | | | | | 3900.00 |
| 0.229 | 2400.00 | 550.00 | 1429120.0 | 11300 | | | | | | 6850.00 |
| 0.228 | 2400.00 | 548.00 | 1423460.0 | 11300 | | | | | | 6830.00 |
| 0.20 | 2360.00 | 481.00 | 1182160.0 | 12300 | | | | | | 5670.00 |
| 0.236 | 3200.00 | 756.00 | 2598400.0 | 11000 | | | | | | 12400.00 |
| 0.2875 | 3200.00 | 920.00 | 3072000.0 | 8750 | | | | | | 14700.00 |
| 0.33 | 3200.00 | 1080.00 | 3584000.0 | 8595 | | | | | | 17203.00 |