



## • HO-12&15 Series



The HO-12 series oscillator is TTL/HCMOS compatible HO-15 series is with 3.3V powersupply voltage. The metal package with pin #7 case ground acts as shielding to minimize EMI radiation.

### FEATURES


- TTL/HCMOS Output compatible
- 14 Pin Full Size
- Industry Standard
- Wide Frequency Range
- Low Cost
- Resistance Weld Package
- 3.3V available

## Electrical Specifications


Parameter		Condition	HO-12	HO-15
Frequency Range	F <sub>o</sub>		0.5MHz~100.00MHz	0.5MHz~125.00MHz
Frequency Stability*		All Condition*	±25ppm, ±50ppm, ±100ppm	
Operating Temperature Range	T <sub>OPR</sub>		0°C~70°C(-40°C~+85°C option)	
Storage Temperature Range	T <sub>STG</sub>		-55°C~+125°C	
Power supply Voltage	V <sub>DD</sub>		5.0V+/-10%	3.3V+/-10%
Aging(First Year)		25°C ±3°C	±5ppm	
Supply Current	I <sub>DD</sub>	0.5MHz to 23.999MHz	20mA Max	15mA Max
		24.000MHz to 49.999MHz	30mA Max	20mA Max
		50.000MHz to 69.999MHz	40mA Max	30mA Max
		70.000MHz to 125.000MHz	60mA Max	45mA Max
Output Symmetry	Sym	1/2V <sub>DD</sub>	40/60%(45/55% Option)	
Rise time	T <sub>r</sub>	10%V <sub>DD</sub> ~90%V <sub>DD</sub>	10 nS Max	8 nS Max
Fall Time	T <sub>f</sub>	90%V <sub>DD</sub> ~10%V <sub>DD</sub>	10 nS Max	8 nS Max
Output Voltage	V <sub>OH</sub>		90% V <sub>DD</sub> min	
	V <sub>OL</sub>		10% V <sub>DD</sub> max	
Output load	TTL Load		1~10TTL	1~5TTL
	HCMOS Load		~50M:50pF ~70M:30pF ~100M:15pF	~50M:30pF ~125M:15pF
Start-up Time		T <sub>s</sub>	10mS Max	

\*Include: 25°C tolerance, operating temperature range, input voltage change, aging, load change, shock and vibration


## Mechanical Dimensions(mm)



## HCOMS Test Circuit



## HOCMS Output Waveform



### TAIWAN:

HOSONIC ELECTRONIC CO., LTD.  
23-1 LANE 84. CHUN YING ST. SHULIN CHEN.  
TAIPEI 23804. TAIWAN. R.O.C.

☎: 886-2-86875200  
☎: 886-2-26816456

WEB SITE:<http://www.hosonic.com.tw>

### CHINA:

HANGZHOU HOSONIC ELECTRONIC CO., LTD.  
XUNSHAN LIANGZHU TOWN MOGANSHAN ROAD  
HANGZHOU, ZHEJIANG, CHINA

☎: (86)-571-88778189  
☎: (86)-571-88778857

Specifications are subject to change without notice