



SPECIFICATION

1. Rated Voltage 1.5VDC
2. Operating Voltage 1.3~2VDC
3. Max. Rated Current 25mA at 1.5VDC
4. Rated Trigger Voltage..... 1.5VDC
5. Min. Sond Pressure Level..... $\leq 1\text{ma}$
6. Resonant Frequency 400 \pm 100Hz
7. Min. Sound Pressure Level..... 70dB at 20VDC/1.5cm
8. Case Material/Color ABS /Black
9. Operating Temperature -20~+60°C
10. Store Temperature -30~+70°C
11. Weight 8g

KEPO NINGBO KEPO ELECTRONIC CO.,LTD
<http://www.chinaacoustic.com>

Magnetic Buzzer
 KPMB-2315P4

No.	DESCRIPTION	APPROVED	DATE	UNIT	SCALE	DWGNO	SHEET	VER
1. 100% INSPECTION 2. 100% TESTING 3. 100% PACKING 4. 100% SHIPPING		DRAWN		mm		KP3, 8,40, 6,47, 01		1.0
5. 100% TESTING 6. 100% PACKING 7. 100% SHIPPING		CHECKED		mm		KP3, 8,40, 6,47, 01		1.0
8. 100% TESTING 9. 100% PACKING 10. 100% SHIPPING		APPROVED		mm		KP3, 8,40, 6,47, 01		1.0
11. 100% TESTING 12. 100% PACKING 13. 100% SHIPPING		DATE		mm		KP3, 8,40, 6,47, 01		1.0