



Specifications

1. Rated Voltage..... 12Vp-p Square Wave
2. Max. Allowable Voltage..... 30Vp-p Square Wave
3. Max. Rated Current..... 4mA at 12Vp-p/1.0KHz
4. Min. Sound Pressure Level..... 80dB at 12Vp-p/1.0KHz/30cm
5. Resonant Frequency..... 1.0±0.5KHz
6. Capacitance at 120Hz..... 70000pF±30%
7. Case Material..... ABS
8. Operating Temperature..... -20~+60°C
9. Store Temperature..... -30~+70°C
10. Weight..... 10g

Compliance with ROHS			
KEPO NINGBO KEPO ELECTRONIC CO.,LTD http://www.chinaacoustic.com			
No.	DESCRIPTION	APPROVED	DATE
TOTAL BUSINESS		APPROVALS	DATE
SOLD OTHERWISE			
XXX #	DRAWN		
XX #	CHECKED	水成锋	
90° ANGLE 4.5°	APPROVED	梁树梁	10.06.11
FIRST ANGLE PROJECTION			
UNIT	SCALE	DWG NO.	SHEET
mm	NOT TO SCALE	OEM1082R	VER 1.0
Piezo Transducer		QUARTZ-1	
KPR-G4420-1082			