



## SPECIFICATION

1. Rated Voltage .....12Vp-p Square Wave
2. Max. Allowable Voltage .....30Vp-p Square Wave
3. Max. Rated Current .....2mA at 4.0KHz/12Vp-p Square Wave
4. Min. Sound Pressure Level.....85dB at 4.0KHz/12Vp-p Square Wave/10cm
5. Capacitance at 100Hz .....15000pF±30%
6. Resonant Frequency .....4.0±0.5KHz
7. Shell Material/Color.....PPS/Black
8. Operating Temperature .....-20~+80°C
9. Store Temperature .....-30~+100°C
10. Weight .....1.5g

				<b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
No.		DESCRIPTION	APPROVED	DATE	<b>Piezo transducer QUARTZ-1 LTD SPT-1750-1713</b>
			APPROVALS	DATE	
TOLERANCES UNLESS NOTED OTHERWISE: X .# .XX .# .XXX .# 90° FORMED -2° ANGLES -4° FIRST ANGLE PROJECTION		DRAWN			UNIT
		CHECKED			mm
		APPROVED		05.08.01	SCALE
					NOT TO SCALE
					SHEET
					VER 1.0
					DWGNO. OEM1713