

规格书编号

SPEC NO :

产品规格书

SPECIFICATION

CUSTOMER 客户: _____
PRODUCT 产品: _____ Plastic Spacer _____
MODEL NO 型号: _____ 49S-SMD Plastic Spacer _____
PREPARED 编制: _____ LEO _____ CHECKED 审核: _____ YORK _____
APPROVED 批准: _____ LIUMING _____ DATE 日期: _____ 2015-12-11 _____

客户确认 CUSTOMER RECEIVED:		
审核 CHECKED	批准 APPROVED	日期 DATE

无锡市好达电子有限公司
Shoulder Electronics Limited

No	DESCRIPTION	CONTENTS
1	Density 密度	1.65~1.96 g/cm ³
2	Melting Point 熔点	288°C
3	Pull Intensity 拉伸强度	>130MPa
4	Shrinkage Rate 断裂伸长率	<1.0%
5	Electric Intensity 介电强度	18Kv/mm
6	Volume Resistance Rate 体积电阻率	>10 ¹⁵ Ω.cm
7	Surface Resistance Rate 表面电阻率	>10 ¹⁶ Ω
8	Resistance Heat 热变形温度	265°C (10Sec)
9	raw material	Plastic

DIMENSIONS (Unit:mm)

